

Mounting Height

The minimum recommended clearance needed to properly mount the caster. Measured with the wheel fully retracted.

○ Green ring = the wheel's 360° swivel path. Keep this area clear.



R8

8 Series Side Mount

Bolts onto the side of a leg, rail or frame.

Mounting height

6 7/8"

Wheel diameter

2 1/2"

Capacity, set of 4

800 lb

Capacity per caster

200 lb

T8

8 Series Top Mount

Bolts up underneath a rail, cross-member or shelf.

Mounting height

6 7/8"

Wheel diameter

2 1/2"

Capacity, set of 4

800 lb

Capacity per caster

200 lb

R7

7 Series Side Mount

Bolts onto the side of a leg, rail or frame.

Mounting height

6"

Wheel diameter

2"

Capacity, set of 4

600 lb

Capacity per caster

150 lb

T7

7 Series Top Mount

Bolts up underneath a rail, cross-member or shelf.

Mounting height

6"

Wheel diameter

2"

Capacity, set of 4

600 lb

Capacity per caster

150 lb

T6

6 Series Top Mount

Bolts up underneath a rail, cross-member or shelf.

Mounting height

4"

Wheel diameter

1 1/2"

Capacity, set of 4

400 lb

Capacity per caster

100 lb